



RoHS Compliant

Features

- Reference frequency for telecommunication systems
- Reflow compatible
- Using ceramic package resulting in high reliability

Applications

- Mobile Communications, Bluetooth®, Wireless LAN

* Bluetooth® Trademarks are owned by Bluetooth SIG Inc.

How to Order

CX2520DB 26000 □□ □ □ □ □ □
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Frequency
- ③ Load Capacitance
- ④ Frequency Stability
- ⑤ Operating Temp. Range
- ⑥ Frequency Temp. Stability
- ⑦ Individual Specification

B0	6 pF	—	F	$\pm 10 \times 10^{-6}$	Std.
D0	8 pF	Std.	G	$\pm 15 \times 10^{-6}$	—
FF	-20 to +70°C			$\pm 10 \times 10^{-6}$	—
LJ	-30 to +85°C			$\pm 15 \times 10^{-6}$	Std.

Packaging (Tape & Reel 3000/ 1000 pcs./ reel)

Specifications

Item	Symbol	Specification	Units	Remarks
Series	—	CX2520DB	—	
Frequency Range	f _{nom}	16000 to 54000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	
Frequency Stability	f _{tol}	±10	$\times 10^{-6}$	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T _{use}	-30 to +85	°C	
Storage Temp. Range	T _{stg}	-40 to +85	°C	
Frequency Temp. Characteristics	f _{tem}	±15	$\times 10^{-6}$	Freq. deviation from the value at 25°C

• Please contact us for other specifications.

Typical Frequencies and Part Numbers

Frequency (kHz)	Part Number
19200.000	CX2520DB19200D0FLJZ1
26000.000	CX2520DB26000D0FLJZ1
27120.000	CX2520DB27120D0FLJZ1
37400.000	CX2520DB37400D0FLJZ1
38400.000	CX2520DB38400D0FLJZ1
40000.000	CX2520DB40000D0FLJZ1
48000.000	CX2520DB48000D0FLJZ1

Table1 Motional Series Resistance


Frequency Range	Motional Series Resistance
16000 to 19199kHz	100Ω max.
19200 to 25999kHz	80Ω max.
26000 to 29999kHz	60Ω max.
30000 to 54000kHz	50Ω max.

Table2 Level of Drive

Frequency Range	Level of Drive
16000 to 54000kHz	10μW (100μW max.)

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

