


OW-M Type 5.0 x 3.2mm SMD LVPECL/LVDS Crystal Oscillator



RoHS Compliant


FEATURE

- Industry Standard 5.0 x 3.2 hermetically sealed ceramic package
- Very low phase jitter: < 1 pS (0.6 pS, typ.) RMS
- Any frequency between 8 MHz and 1500 MHz
- Tri-state enable/disable
- Fast delivery


TYPICAL APPLICATION

- High-Speed Gigabit Ethernet, Fiber Channel, Storage Area Network, SONET
- Enterprise Server, SAS/SATA
- Microprocessors/DSP/FPGA
- Broadband Access
- Smart Grid

DIMENSION(mm)



SOLDER PAD LAYOUT (mm)



ELECTRICAL SPECIFICATION

Parameter	LVPECL				LVDS				Unit
	3.3V		2.5V		3.3V		2.5V		
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
Supply Voltage Variation (VDD) ±5%	3.135	3.465	2.375	2.625	3.135	3.465	2.375	2.625	V
Frequency Range	8	1500	8	1500	8	1500	8	1500	MHz
Standard Frequency	106.25, 125, 133.33, 150, 155.52, 156.25, 187.5, 212.5, 312.5, 622.08								MHz
Supply Current 8 MHz ≤ Fo ≤ 1500 MHz	-	50	-	50	-	50	-	50	mA
Output Level Output High (Logic "1")	2.275	-	1.475	-	-	1.6	-	1.6	V
Output Low (Logic "0")	-	1.68	-	0.88	0.9	-	0.9	-	V
Transition Time : Rise/ Fall Time*	-	1.0	-	1.0	-	1.0	-	1.0	nSec
Start Time	-	10	-	10	-	10	-	10	mSec
Tri-State(Input to Pin 2 or Pin 1)									
Enable (High voltage or floating)	2.31	-	1.75	-	2.31	-	1.75	-	V
Disable (Low voltage or GND)	-	0.99	-	0.75	-	0.99	-	0.75	V
RMS Phase Jitter (Integrated 12 kHz ~ 20 MHz)	-	1.0	-	1.0	-	1.0	-	1.0	pSec
Phase Noise @156.25 MHz									
100 Hz	-	-85	-	-85	-	-85	-	-85	dBc/Hz
1 kHz	-	-105	-	-105	-	-105	-	-105	
10 kHz	-	-115	-	-115	-	-115	-	-115	
Aging (@25°C 1st year)	-	±3	-	±3	-	±3	-	±3	ppm
Storage Temp. Range	-55	125	-55	125	-55	125	-55	125	°C

+Transition times are measured between 20% and 80% of VDD

FREQ. STABILITY vs. TEMP. RANGE

Temp. (°C)	ppm	
	±25	±50
-10 ~ +60	○	○
-20 ~ +70	○	○
-40 ~ +85	△	○

* ○ : Available △:Conditional X: Not available

* Inclusive of calibration @ 25 °C, operating temperature range, input voltage variation, load variation, aging (1st year), shock, and vibration

Note: not all combination of options are available. Other specifications may be available upon request.

Rev(3)05/2015

www.taitien.com

sales@taitien.com.tw

Specifications subject to change without notice.